



TECHNICAL REQUIREMENTS:

1. MECHANICAL:
 - 1.1 WITHDRAWAL FORCE AFTER 2000 CYCLES: 39.2N MAX,9.8N Min.
 - 1.2 WITHDRAWAL FORCE AFTER 2001-10000 CYCLES:4.9N Min,39.2N Max.
 - 1.3 INSERTION FORCE:44.1N Max.
2. ELECTRICAL:
 - 2.1 CONTACT CURRENT RATING: 0.5A MIN.
 - 2.2 VOLTAGE RATING: 40V AC(RMS)
 - 2.3 WITHSTANDING VOLTAGE:
 - 500 VOLTS AC BETWEEN ADIACENT TERMINAL(UNMATE)
 - 300 VOLTS AC BETWEEN ADIACENT TERMINAL(MATE)
 - 2.4 INSULATION RESISTANCE:
 - 100 MOHM MIN.(UNMATED); 10 MOHM MIN.(MATED)
 - 2.5 CONTACT RESISTANCE: 30 MILLIOHMS MAX.
3. ENVIRONMENTAL:
 - 3.1 OPERATING TEMPERATURE: -25℃ to +85℃
 - 3.2 STORAGE TEMPERATURE: 20℃ TO 25℃

1	HOUSING	LCP BLACK UL94V-0	③
19	CONTACT	COPPER ALLOY, GOLD FLASH PLATED ON CONTACT AREA TIN PLATING ON SOLDER AREA, NI PLATING UNDER OVER ALL	②
1	SHELL	SPCC/BRASS ,NI PLATING OVER ALL.	①
QTY'S	PART	SPECIFICATION	ITEM

版本 千川	變更內容 MODIFIXATION	日期 DATE	 東莞市千川电子有限公司 DONG GUAN QIAN CHUAN ELECTRONIC CO., LTD	公差 TOLERANCE	數量 QUANTITY	制圖 DRAWIN	潘红国	品名 TITLE	HDMI 19Pin 母座 卧式三排DIP 无柱 四脚插板 后鱼叉脚			
				.X ± 0.38	單位 UNIT	mm	審核 CHECKED	LHS	料號 PART NO.	QHMFCB2-01SN0P9		
				.XX ± 0.25	比例 SCALE	1:1	核准 APPROVE	LHL	材質 MATERIAL	圖号 DRAW NO.		
				.XXX ± 0.10	圖幅 SIZE	A4	角法 PROJ.		頁數 SHEET	1 OF 1	顏色 COLOR	
			X° ± 2°									
			X° ± --									