


TECHNICAL REQUIREMENTS:

1. MECHANICAL:
 - 1.1 WITHDRAWAL FORCE AFTER 2000 CYCLES: 39.2N MAX,9.8N Min.
 - 1.2 WITHDRAWAL FORCE AFTER 2001-10000 CYCLES: 4.9N Min,39.2N Max.
 - 1.3 INSERTION FORCE: 44.1N Max.
2. ELECTRICAL:
 - 2.1 CONTACT CURRENT RATING: 0.5A MIN.
 - 2.2 VOLTAGE RATING: 40V AC(RMS)
 - 2.3 WITHSTANDING VOLTAGE:
 - 500 VOLTS AC BETWEEN ADIACENT TERMINAL(UNMATE)
 - 300 VOLTS AC BETWEEN ADIACENT TERMINAL(MATE)
 - 2.4 INSULATION RESISTANCE:
 - 100 MOHM MIN.(UNMATED); 10 MOHM MIN.(MATED)
 - 2.5 CONTACT RESISTANCE: 30 MILLIOHMS MAX.
3. ENVIRONMENTAL:
 - 3.1 OPERATING TEMPERATURE: -25℃ to +85℃
 - 3.2 STORAGE TEMPERATURE: 20℃ TO 25℃

1	HOUSING	LCP BLACK UL94V-0	③
19	CONTACT	COPPER ALLOY, GOLD FLASH PLATED ON CONTACT AREA TIN PLATING ON SOLDER AREA, NI PLATING UNDER OVER ALL	②
1	SHELL	SPCC/BRASS ,Ni PLATING OVER ALL.	①
QTY'S	PART	SPECIFICATION	ITEM

版本 千川	變更內容 MODIFIXATION	日期 DATE
00	新整理	2020.08.20

 東莞市千川电子有限公司
DONG GUAN QIAN CHUAN ELECTRONIC CO., LTD

公差 TOLERANCE	數量 QUANTITY	制圖 DRAW/IN	P_H_G	品名 TITLE	HDMI 19Pin 母座 夾板式SMT 夾板厚度1.60mm			
.X ± 0.30	單位 UNIT	審核 CHECKED	TOMS	料號 PART NO.	QHME1-GFSNOP12			
.XX ± 0.25	比例 SCALE	核准 APPROVE	LGL	材質 MATERIAL	圖號 DRAW NO.			
.XXX ± 0.15	圖幅 SIZE	角法 PROJ.		頁數 SHEET	1 OF 1	顏色 COLOR		
X° ± 2°								
.X° ± --								