



TECHNICAL REQUIREMENTS:

1. ELECTRICAL:

- CURRENT RATING: 3AMPS.
- VOLTAGE RATING: 500VAC.
- CONTACT RESISTANCE: 30mΩ MAX.
- INSULATION RESISTANCE: 1000mΩ

2. ENVIRONMENTAL:

- OPERATING TEMPERATURE: -25°C to +85°C
- STORAGE TEMPERATURE: 20°C TO 25°C

| | | | |
|-----------------|------|------------------------------------|------|
| SHIELDING SHELL | 1 | SPCC, Ni PLATING OVER ALL. | ⑦ |
| FISH FORK | 2 | SPCC, Tin PLATING OVER ALL. | ⑥ |
| SHELL | 1 | SPCC, Ni PLATING OVER ALL. | ⑤ |
| RIVET | 2 | COPPER ALLOY, Ni PLATING OVER ALL. | ④ |
| COVER | 1 | PA66+30%G. F | ③ |
| CONTACT | 24 | BRASS, SEMI-GOLD TIN | ② |
| INSULATOR | 1 | PBT+30%G. F | ① |
| PART NAME | QTY. | MATERIAL | ITEM |

| 版本 | 變更內容 | 日期 |
|----|--------------|------|
| 千川 | MODIFIXATION | DATE |
| | | |
| | | |



東莞市千川电子有限公司
DONG GUAN QIAN CHUAN ELECTRONIC CO., LTD

| | | | | | | | |
|-------------|----------|---------|------|----------|--|----------|--|
| 公差 | 數量 | 制圖 | 潘红国 | 品名 | DV124+1 母座 卧式DIP 黑/白胶 带屏蔽壳 短柱铆合 锁螺丝 | | |
| TOLERANCE | QUANTITY | DRAWIN | | TITLE | | | |
| .X ± 0.35 | 單位 | 審核 | Toms | 料號 | QDV1CW3-01LB0P | | |
| .XX ± 0.25 | UNIT | CHECKED | | PART NO. | | | |
| .XXX ± 0.20 | 比例 | 核准 | LGL | 材質 | | 图号 | |
| X° ± 2° | SCALE | APPROVE | | MATERIAL | | DRAW NO. | |
| .X° ± -- | 圖幅 | 角法 | | 頁數 | 1 OF 1 | 顏色 | |
| | SIZE | PROJ. | | SHEET | | COLOR | |